



ELECTRICALLY HEATED HIGH-PRESSURE CLEANING SYSTEMS



ES543K472A
5.4 gpm @ 3000 psi max.



ES830K2472AS - 8 gpm @ 3000 psi
with optional SRA surge relief assembly



ES543K472AS - 5.4 gpm @ 3000 psi
with optional stainless steel wrap, cart and
dual chemical system



ES650K2496A - 6gpm @ 5000 psi
with heavy-duty lifting skid


MODEL (Specs for 60hz)	Flow GPM	Pressure PSIG	Heater Input	Motor H.P.	Total 208V	Amps 460V	-3 Phase 600V	Dimensions L" x W" x H"
ES411K424A	4	1100	24 kW	3	72.5	34.3	26.6	32/24/52
ES411K448A	4	1100	48 kW	3	134.8	64.4	49.7	32/24/52
ES411K472A	4	1100	72kW	3	209.9	94.5	72.4	32/24/52
ES420K424A	4	2000	24 kW	5	77.1	36.8	28.4	32/24/52
ES420K448A	4	2000	48 kW	5	139.6	66.9	51.8	32/24/52
ES420K472A	4	2000	72 kW	5	-	97	74.4	32/24/52
ES429K424A	4	2900	24 kW	7.5	89.2	39.9	31.3	32/24/52
ES429K448A	4	2900	48 kW	7.5	155.9	70	54.4	32/24/52
ES429K472A	4	2900	72 kW	7.5	-	100.2	76.9	32/24/52
ES440K448A	4	4000	48 kW	10	162.4	72.8	56.7	32/24/52
ES440K472A	4	4000	72 kW	10	-	102.9	79.9	32/24/52
ES450K448A	4	5000	48 kW	15	-	78.4	60.7	38/28/55 ⁽¹⁾
ES450K472A	4	5000	72 kW	15	-	108.6	83.9	38/28/55 ⁽¹⁾
ES550K448A	5	5000	48 kW	20	-	85.2	66.5	38/28/55 ⁽¹⁾
ES550K472A	5	5000	72 kW	20	-	115.4	89.8	38/28/55 ⁽¹⁾
ES543K448A	5.4	3000	48 kW	10	162.4	72.8	56.7	32/24/52
ES543K472A	5.4	3000	72 kW	10	-	102.9	79.9	32/24/52
ES562K448A	5.6	2000	48 kW	7.5	155.9	66.9	54.4	32/24/52
ES562K472A	5.6	2000	72 kW	7.5	-	97	77.6	32/24/52
ES612K448A	6	1200	48 kW	5	147.9	66.9	51.8	32/24/52
ES620K448A	6	2000	48 kW	7.5	155.9	70	54.4	32/24/52
ES620K472A	6	2000	72 kW	7.5	-	100.2	77.6	32/24/52
ES812K2448A*	8	1200	48 kW	7.5	155.9	70	54.4	53/48/40
ES812K2472A*	8	1200	72 kW	7.5	-	100.2	77.6	53/48/40
ES820K2448A*	8	2000	48 kW	10	162.4	72.8	56.7	53/48/40
ES820K2472A*	8	2000	72 kW	10	-	102.9	79.9	53/48/40
ES830K2448A*	8	3000	48 kW	15	173.4	78.4	60.7	53/48/40
ES830K2472A*	8	3000	72 kW	15	-	108.6	83.9	53/48/40
ES1225K24115A*	12	2500	115 kW	20	-	169.4	131.4	53/48/40
ES1030K2472A*	10	3000	72 kW	20	-	115.4	89.8	53/48/40
ES1030K2496A*	10	3000	96 kW	20	-	145.5	113.1	53/48/40
ES1030K24115A*	10	3000	115 kW	20	-	169.4	131.4	53/48/40

* includes dual heat exchanger coils, 2 single lance gun assemblies/2 high-pressure wash hoses for multi-gun operation.
⁽¹⁾ pumping system top-mounted on heat exchanger (32" x 24" footprint)

STANDARD EQUIPMENT:

- Belt-driven General ceramic plunger pump with adjustable pressure regulator, pilot-activated flow switch, liquid-filled pressure gauge and thermal protection (automatic shutdown)
- Powder coat painted heavy-gauge carbon steel base and frame assemblies
- Powder coat painted heater wraps and pump covers
- Automatic heat exchanger with #316 stainless steel HX coil(s), pin-type Calrod heating elements with Incoloy sleeves, adjustable temperature controller, low level switch with indicator light and NEMA 4X-rated control switches
- Dual or single lance/gun(s) with 50 ft. high-pressure wash hose(s) and high-pressure (upstream) or low-pressure (downstream) chemical injection

CONSIDER THE ADVANTAGES OF A PSC ELECTRICALLY HEATED PRESSURE CLEANING SYSTEM...



FUNCTIONAL DESIGN:

- *Ease of use* - trigger gun controlled start/stop system with solid state time delay shutdown
- *Instant hot water* - heat exchanger is thermally insulated allowing for almost 100% energy input/output and continuous, efficient operation
- *Large 70 gallon (single coil models) & 130 gallon (dual coil models) heater storage tanks* - allows for continuous heat recovery even when trigger gun(s) not in use
- *No open flame* - can be installed in virtually any location
- *Inherent pump protection* - automatic high temperature shut down (thermo-probe) on pump bypass
- *Compact* - 24" x 32" footprint with 52" height (single coil models)

RELIABLE PERFORMANCE:

- *Low-rpm, belt-driven, oil-bath plunger pump* - longer pump life when compared to direct drive systems
- *Flow switch activated* - not affected by small system leaks (i.e. trigger gun)
- *#316 stainless steel heat exchanger coil(s)* - designed for continuous-duty use
- *No direct immersion of heating elements* - no scale buildup or element burnout

VERSATILE:

- *1000 psi to 5000 psi – 2 gpm to 16 gpm*
- *Ideal centralized cleaning system*
- *Standard and explosion-proof models*
- *Full range of factory added options incl. portability carts, low and high-pressure surge arrestors, stainless steel frames and covers*
- *208, 230, 440-480, 550-600 VAC/3 phase/60 hz and 220, 380-600 VAC/3 phase/50 hz models available*
- *24, 36, 48, 60, 72, 96 115, and 144kW input heat exchangers (custom-made models up to 230 kW)*
- *ASME B31.1, 2004 (Power Piping) code-compliant models available*

COST EFFECTIVE:

- *Low installation cost* - no venting required, can be installed virtually anywhere
- *Low maintenance costs* - heat exchanger coil does not require decalcification, only periodic pump oil changes required
- *Low operating costs* - compares favorably with fuel-fired and gas-fired machines and requires less kW input than direct-immersion type electrically heated models

EASE OF MAINTENANCE:

- *Pump/motor/controls/coil(s) easily accessible*
- *No water/soap scale buildup* - skin temperature of heat exchanger coil never exceeds 190°F

SAFETY:

- *Vented-to-atmosphere heat exchanger design*
- *Low heat exchanger solution cut-off switch with indicator light*
- *Adjustable temperature controller*
- *CSA approved*

SUPPORT:

- *Special application-designed systems*
- *Backed by qualified and responsive sales and technical personnel*

