

PRESSURE REGULATORS AND UNLOADERS



FLOW SENSITIVE UNLOADER VALVES



- MAXIMUM 3000 PSI / 165°F
- INLET 3/8 IN. BSPF
- OUTLET 3/8 IN. BSPM
- BY-PASS 3/4 IN. BSPM/F

PART NO.	FLOW RANGE
240196	2.1 TO 3.0 GPM
240197	3.0 TO 4.2 GPM
240198	4.2 TO 6.6 GPM
240199	6.6 TO 10.8 GPM
240200	2.5 TO 13.2 GPM

REGULATING VALVE



- PART NO. 240095
- MAXIMUM 870 PSI / 165°F
- MAXIMUM FLOW 53 GPM
- INLET 3/4 IN. BSPF
- OUTLET 1/2 IN. BSPF
- BY-PASS 1 IN. BSPF

PN:220022 PRESSURE REDUCTION VALVE




- REDUCES INLET PRSSURE FROM MAX. 400 PSI TO 15-75 PSI
- MAXIMUM 10 GPM / 160°F
- INLET & OUTLET 3/4 IN. FGHT

BALANCED RELIEF VALVE



- PART NO. 240096
- RATED 3200 PSI/MAX. 3600 PSI
- MAXIMUM FLOW 6.3 GPM
- MAXIMUM TEMP. 195°F
- INLET (2) 3/8 IN. BSPF
- BY-PASS 3/8 IN. BSPF

SAFETY RELIEF VALVE



- PART NO. 209016
- FOR USE ON SYSTEMS WITH UP TO 3000 PSI WORKING PRESSURE
- REQUIRES ADJUSTMENT TO ± 300 PSI ABOVE WORKING PRESSURE
- BRASS BODY WITH STAINLESS STEEL PISTON AND SPRING
- 1/2 IN. NPTM CONNECTION WITH SET SCREW AND 3/8 IN. HOSE BARB

FLOW AND PRESSURE SWITCHES



200781 FLOW SWITCH



- GRAVITY ACTUATED
- MAXIMUM 3600 PSI / 8 GPM / 176 °F
- MAXIMUM 400 VOLTS / 3.0 AMPS (100 WATTS)
- INLET / OUTLET - 3/8 IN. FNPT X 3/8 IN. FNPT

AL680 PRESSURE SWITCH



- MAXIMUM PRESSURE 3650 PSI
- SWITCH PRESSURE 435 PSI
- MAXIMUM TEMPERATURE 200 °F
- VOLTAGE 12 - 250 VOLT

240094

THROTTLE CONTROL



- THROTTLE CONTROL FOR GASOLINE ENGINES
- RATED PRESSURE 725 PSI
- MAXIMUM PRESSURE 3000 PSI

240036 FLOW SWITCH



- SPRING ACTUATED WITH PILOT FEATURE
- MAXIMUM 4000 PSI / 165 °F
- 0.75 GPM TO 6 GPM FLOW RATE - +6 GPM REQUIRES BY-PASS
- MAXIMUM 250 VOLTS / 3.0 AMPS
- INLET / OUTLET - 3/8 IN. FNPT X 3/8 IN. FNPT
- ALL STAINLESS STEEL VERSION - PART NO. 400670

200893 PRESSURE SWITCH



- ADJUSTABLE RANGE: DECREASING - MIN. .5 PSI MAX. 14.5 PSI / INCREASING - MIN. .6 PSI AMX. 15 PSI
- ELECTRICAL CONNECTION 1/2 IN. NPS CONDUIT CONNECTION TO SCREW TERMINALS ON SWITCH
- PRESSURE CONNECTION 1/4 IN. NPTF
- 24 VAC TO 250 VAC

202188 FLOW SWITCH



- SPRING ACTUATED
- MAXIMUM 3600 PSI / 8 GPM / 176 °F
- MAXIMUM 400 VOLTS / 3.0 AMPS (100 WATTS)
- INLET / OUTLET - 3/8 IN. FNPT X 3/8 IN. MNPT

PRESSURE GAUGES

GLYCERIN FILLED PRESSURE GAUGES



- STAINLESS STEEL CASE WITH BRASS INTERNALS AND 2 IN. DIAMETER ACRYLIC WINDOW
- ACCURACY ± 1.5% OF SPAN

PART NO.	PRESSURE RANGE
220255	0 - 200 PSI
201487	0 - 2000 PSI
201488	0 - 3000 PSI
220039	0 - 4000 PSI
201489	0 - 5000 PSI