

DRIVE COMPONENTS



PUMP PULLEYS



- A PULLEYS - 2 GROOVE CAST ALUMINUM
- 24 MM BORE
- 201441 - 100 MM - 3.9 PITCH
- 201442 - 140 MM - 5.5 PITCH
- 201443 - 160 MM - 6.3 PITCH

GEAR REDUCERS



PSC HAS A FULL LINE OF COMPONENTS AVAILABLE FOR VIRTUALLY ANY DRIVE-SYSTEM CONFIGURATION. CONTACT OUR CUSTOMER SERVICE DEPARTMENT FOR PRICING AND ASSISTANCE IN DETERMINING THE IDEAL COMPONENT PART(S) FOR YOUR REQUIREMENTS.

HIGHER PRESSURE RANGE GAUGES AVAILABLE

CLUTCH DRIVES



TEMPERATURE CONTROLLERS



240179 FLOW-THROUGH THERMOSTAT




- MAXIMUM 3000 PSI / 12 GPM
- 50 °F TO 300 °F RANGE - FACTORY PRESET FOR MAXIMUM 200 °F
- INLET & OUTLET 1/2 IN. NPTF

PROBE-STYLE THERMOSTAT



- 86 °F TO 194 °F RANGE - PART NO. 240042
- 86 °F TO 302 °F RANGE - PART NO. 240046
- MAXIMUM 4000 PSI / 380 VOLT / 4 AMPS

403060 PROBE-STYLE THERMOSTAT (WELL 403059)




- 100 °F TO 240 °F RANGE
- 5 °F TO 45 °F DIFFERENTIAL
- 4 IN. PROBE WELL WITH 1/2 IN. NPTM FITTING - CONVERTIBLE FROM HORIZONTAL TO VERTICAL
- FOR USE IN 24, 120 & 240 VOLT CIRCUITS

ACCUMULATORS/PULSATION DAMPENERS



SRA SURGE RELIEF ASSEMBLY



- SHOULD BE INSTALLED ON THE WATER SUPPLY LINE WHEN THE SUPPLY LINE HAS A BACKFLOW PREVENTER, PRESSURE REDUCING OR CHECK VALVE PRESENT
- MAXIMUM 150 PSI / 200 °F
- 40 PSI AIR PRECHARGE - RECHARGEABLE
- FACTORY SET SAFETY RELIEF VALVE
- INLET/OUTLET 3/4 IN. M X 3/4 IN. F GARDEN HOSE FITTINGS

PDH PULSATION DAMPENER



- RATED MAXIMUM 10 GPM / 3000 PSI / 175 °F
- 21 CU. IN. CAPACITY
- 580 PSI DRY NITROGEN PRECHARGE - RECHARGEABLE
- CARBON STEEL CONSTRUCTION

6028 PULSATION DAMPENER



- RATED MAXIMUM 15 GPM / 3000 PSI / 180 °F
- 10 CU. IN. CAPACITY
- 450 PSI DRY NITROGEN PRECHARGE - SEALED

CONTACT OUR CUSTOMER SERVICE DEPARTMENT FOR INFORMATION AND PRICING ON ACCUMULATORS AND PULSATION DAMPENERS RANGING UP TO 120 CU. IN. CAPACITY