

STRAINERS & FILTERS



201470 GARDEN HOSE FILTER WASHER



- STAINLESS STEEL SCREEN

SUCTION FILTER



- 206540 WITH 3/4 IN. & 1 IN. HOSE BARB
- 206541 WITH CHECK VALVE AND 3/4 IN. & 1 IN. HOSE BARB
- 20 MESH INTAKE SCREEN

WFI INLINE FILTER



- ALUMINUM BODY WITH 50 MESH STAINLESS STEEL SCREEN
- MAXIMUM 145 PSI / 5.8 GPM / 175 °F
- INLET X OUTLET 1/2 IN. BSP-F X 1/2 IN. BSP-M

7100 SERIES INLINE FILTERS - ROWI - TYPE

PN:400879



- NYLON BODY WITH 304 SS MESH SCREEN
- INSIDE OUT FLOW DIRECTION ALLOWS SEDIMENT COLLECTION INSIDE OF SCREEN

PART NO.	MAXIMUM FLOW SUCTION/PRESSURE	PORT SIZE	DIMENSIONS INCHES
7104	6 GPM / 10 GPM	1/2 IN.	3.6X2.95X5.35
7105	15 GPM / 20 GPM	3/4 IN.	3.6X2.95X5.35
7106	20 GPM / 25 GPM	1 IN.	5.0X4.1X6.35
7108	60 GPM / 75 GPM	1-1/2 IN.	5.13X4.1X8.13

LUBRICANTS

cat crankcase oil is a special blend, multi-viscosity petroleum based hydraulic lubricant for high pressure hydraulic systems. non-detergent for greater wear and protection at high rpm and pressure. anti-wear, high pressure and oxidizer inhibitor additives for maximum protection and wear. runs significantly cooler than typical lubricants, enhancing the longevity of components.



PART NO.	SIZE
6101	21 U.S. OZ.
6100	12 X 21 U.S. OZ.
6105-1	2.5 U.S. GAL.
6105	2 X 2.5 U.S. GAL.

MISCELLANEOUS ACCESSORIES

JETTER VALVE



- FOR USE IN SEWER CLEANING APPLICATIONS
- REPLACES VALVE CAP

PART NO.	APPLICATION
240176	USE WITH TT SERIES PUMPS
240177	USE WITH EZ SERIES PUMPS
240178	USE WITH 47 SERIES PUMPS

400280 ANALOG HOUR METER



- HIGH QUALITY DESIGN WITH ACCURATE READOUT
- 24 VAC
- 2-3/4 IN. FACE
- 6 COUNT INDICATION INCLUDING 1/10 HOUR

240173 TANK CLEANER



- AIR-DRIVEN
- 4.0 TO 10.5 GPM
- MAXIMUM 2000 PSI
- ROTATING HEAD WITH 4 NOZZLES - FOR SMALL OPENINGS

AT PSC WE STOCK A WIDE RANGE OF ACCESSORIES FOR USE WITH VIRTUALLY ANY BRAND OF PRESSURE WASHER. CONTACT OUR CUSTOMER SERVICE DEPARTMENT IF THE ACCESSORY YOU NEED IS NOT SHOWN IN THIS CATALOGUE.