

Lance assemblies



SLG (SINGLE LANCE GUN) ASSEMBLIES



SLG ASSEMBLY WITH ST1500 TRIGGER GUN,
36" LANCE AND NOZZLE



EZ-SLG ASSEMBLY WITH ST2605 TRIGGER GUN,
36" LANCE AND NOZZLE



SLG-SS ASSEMBLY WITH ST2700 TRIGGER GUN,
36" LANCE AND NOZZLE

DLG (DUAL LANCE GUN) ASSEMBLIES



DLG ASSEMBLY WITH ST1500 TRIGGER GUN,
38" LANCE AND NOZZLES



EZ-DLG ASSEMBLY WITH ST2605 TRIGGER GUN,
38" LANCE AND NOZZLES



DLG-SS ASSEMBLY WITH ST2605 TRIGGER GUN,
40" LANCE AND NOZZLES

*SPECIFY NOZZLE SIZE WHEN ORDERING

NOZZLES



THREADED NOZZLES



- HARDENED STAINLESS STEEL CONSTRUCTION
- 0°, 15°, 25° OR 40° FAN PATTERN
- 1/8" OR 1/4" MNPT THREADS
- SEE PRICE LIST FOR PART NUMBERS

QUICK CONNECT NOZZLES



- HARDENED STAINLESS STEEL CONSTRUCTION
- 0°, 15°, 25° OR 40° FAN PATTERN
- 1/4" QUICK CONNECT DESIGN
- SEE PRICE LIST FOR PART NUMBERS

ROTARY NOZZLES



A

B

- ST357 SERIES (A) MAX. 3000 PSI, 190°F - 1/4" FNPT
- ST457 SERIES (B) MAX. 5000 PSI, 212°F - 1/4" FNPT
- SEE PRICE LIST FOR PART NUMBERS

220370 DOUBLE NOZZLE

HOLDER



- MAXIMUM 2900 PSI / 10.5 GPM / 300°F
- INLET & OUTLETS (2) - 1/4"FNPT

220000 ADJUSTABLE NOZZLE

HOLDER



- MAXIMUM 3600 PSI / 8 GPM / 300°F
- INLET & OUTLET - 1/4"FNPT

MRI ADJUSTABLE NOZZLE



- ADJUSTABLE FAN PATTERN FROM 0° TO 60°
- HIGH OR LOW PRESSURE SELECTION
- MAXIMUM 3000 PSI / 5.5 GPM / 140°F
- INLET SIZE - 1/4" BSP-F

NOZZLE STRAINERS



- MAXIMUM 5000 PSI / 8 GPM / 190°F
- 1/4" FNPT BUSHING
- 1/4" QC PLUG X 1/4" MNPT PART NO. 401626
- 1/4" FNPT X 1/4" MNPT PART NO. 401627

PIPE CLEANING NOZZLES



- EFFECTIVE FOR CLEANING PIPES UP TO 6 IN. DIAMETER

PART NO.	ORFICE SIZE	THREAD SIZE	ROTATING
202961	5.5	1/8 IN. F	NO
201680	4.5	1/4 IN. F	NO
202916	5.5	1/4 IN. F	NO
202917	6.0	1/4 IN. F	NO
202918	7.5	1/4 IN. F	NO

***SBH**

WET SANBLASTING KIT



- FOR WET SANBLASTING - USES DRY AND SIFTED QUARTZ OR SILICA SAND
- WITH 15FT SUCTION HOSE SPIGOT & QUICK CONNECT