


PSC CLEANING SYSTEMS INC.

EXPLOSION-PROOF PRESSURE WASHERS CSA INSPECTED CLASS 1, DIVISION 1, GROUP C & D



S420EA3-EX1 STANDARD SERIES



OS420EA3-EX1 OFF-SHORE SERIES

FEATURES - COLD WATER MODELS:

- BELT-DRIVEN, OIL-BATH PLUNGER PUMP WITH THERMO-PROBE PUMP PROTECTION AND POWDER COAT PAINTED BELT GUARD (STAINLESS STEEL BELT GUARD, DRIP-PROOF PUMP BASE AND LOW INLET WATER PRESSURE PROTECTION ON OS SERIES MODELS)
- TRIGGER GUN ACTIVATED START/STOP CONTROL CIRCUIT WITH SOLID STATE TIME DELAY SHUTDOWN
- CERTIFIED MOTOR, CONDUIT AND JBEW CONTROL BOX
- DUAL LANCE GUN WITH 50 FT. HIGH PRESSURE HOSE AND DOWNSTREAM CHEMICAL INJECTION
- POWDER COAT PAINTED FRAME ASSEMBLY WITH LIFTING EYES AND MOUNTING FEET (OS SERIES MODELS GALVANIZED TO OFF-SHORE SPECIFICATIONS)

MODEL	GPM	PSI	H.P.	VOLTAGE	AMPS
S420EA3-EX1	4.0	2000	5	208/460/575	14.6/6.6/5.3
S429EA3-EX1	4.0	2900	7.5	208/460/575	22.5/10.2/8.2
S440EA3-EX1	4.0	4000	10	208/460/575	29/13.1/10.5

MODEL	GPM	PSI	H.P.	VOLTAGE	AMPS
OS420EA3-EX1	4.0	2000	7.5	208/460/575	22.5/10.2/8.2
OS429EA3-EX1	4.0	2900	10	208/460/575	29/13.1/10.5
OS440EA3-EX1	4.0	4000	15	208/460/575	44.2/20/16



S429K448A-EX1 STANDARD SERIES



OS429K448AS-EX1 OFF-SHORE SERIES

FEATURES - HOT WATER MODELS:

- BELT-DRIVEN, OIL-BATH PLUNGER PUMP WITH THERMO-PROBE PUMP PROTECTION AND POWDER COAT PAINTED PUMP COVER (STAINLESS STEEL PUMP COVER, DRIP-PROOF PUMP BASE AND LOW INLET WATER PRESSURE PROTECTION ON OS SERIES MODELS)
- TRIGGER GUN ACTIVATED START/STOP CONTROL CIRCUIT WITH SOLID STATE TIME DELAY SHUTDOWN
- 48 KW INPUT AUTOMATIC HEAT EXCHANGER WITH STAINLESS STEEL HEATING COIL, LOW WATER LEVEL SHUTDOWN, ADJUSTABLE TEMPERATURE CONTROL AND POWDER COAT PAINTED WRAP (STAINLESS STEEL WRAP ON OS SERIES MODELS)
- 72, 96 & 115 KW INPUT HEAT EXCHANGERS AVAILABLE
- CERTIFIED MOTOR, CONDUIT AND JBEW CONTROL BOX
- DUAL LANCE GUN WITH 50 FT. HIGH PRESSURE HOSE AND DOWNSTREAM CHEMICAL INJECTION
- POWDER COAT PAINTED FRAME ASSEMBLY WITH LIFTING EYES AND MOUNTING FEET (OS SERIES MODELS GALVANIZED TO OFF-SHORE SPECIFICATIONS)

MODEL	GPM	PSI	H.P.	VOLTAGE	AMPS
S420K448A-EX1	4.0	2000	5	460/575	65/52
S429K448A-EX1	4.0	2900	7.5	460/575	68/55
S440K448A-EX1	4.0	4000	10	460/575	70/57

MODEL	GPM	PSI	H.P.	VOLTAGE	AMPS
OS420K448A-EX1	4.0	2000	7.5	460/575	68/55
OS429K448A-EX1	4.0	2900	10	460/575	70/57
OS440K448A-EX1	4.0	4000	15	460/575	76/61



MEMBER OF
CETA

PHONE: (800) 246-9689 / (905) 761-1733 • FAX: (905) 738-6168

WEBSITE: WWW.PSCCLEAN.COM • EMAIL: INFO@PSCCLEAN.COM

© 2002 PSC CLEANING SYSTEMS INC., ALL RIGHTS RESERVED