



PSC CLEANING SYSTEMS INC.

NATURAL GAS / PROPANE HEATED PRESSURE WASHERS



300,000 BTUH INPUT HEATER - PROPANE



330,000 BTUH INPUT HEATER - NATURAL GAS

- 3000 PSI W.P. SCHEDULE 80 HEATING COIL
- STAINLESS STEEL COIL WRAP
- ADJUSTABLE THERMOSTAT
- DUAL LANCE GUN WITH 50 FT. H.P. HOSE

- DOWNSTREAM CHEMICAL INJECTION
- SAFETY RELIEF VALVE
- PNEUMATIC TIRES AND PUSH HANDLE (P30 MODELS)

NATURAL GAS HEATED - ELECTRIC MOTOR DRIVEN

MODEL NO.	FLOW - GPM	PRESSURE - PSI	MOTOR - H.P.	VOLTAGE - PHASE
S315G30E1	3	1500	3	230 - 1
S420G30E1	4	1900	5	230 - 1
S420G30E3	4	1900	5	208/460/575 - 3
S429G30E1	4	2900	7.5	230 - 1
S429G30E3	4	2900	7.5	208/460/575 - 3

PROPANE HEATED - ELECTRIC MOTOR DRIVEN

MODEL NO.	FLOW - GPM	PRESSURE - PSI	MOTOR - H.P.	VOLTAGE - PHASE
P315P30E1	3	1500	3	230 - 1
P420P30E1	4	1900	5	230 - 1
P420P30E3	4	1900	5	208/460/575 - 3
P429P30E1	4	2900	7.5	230 - 1
P429P30E3	4	2900	7.5	208/460/575 - 3

PROPANE HEATED - GAS ENGINE DRIVEN

MODEL NO.	FLOW - GPM	PRESSURE - PSI	H.P.	ENGINE
P315P30G	3	1500	5.5	HONDA
P420P30G	4	2000	9	HONDA
P425P30G	4	2000	11	HONDA
P430P30G	4	3000	13	HONDA

COMMON FACTORY ADDED OPTIONS

- A1, A2, A3 TRIGGER GUN ACTIVATED START/STOP WITH SOLID STATE TIME DELAY SHUT DOWN (ELECTRIC MODELS ONLY)
- TC THROTTLE CONTROL FOR AUTOMATIC ENGINE SPEED REDUCTION (GAS MODELS ONLY)
- TB30-2 DUAL TANK BRACKET FOR 2 X 30 LB. PROPANE CYLINDERS
- SO-P, SO-S STEAM OPTION (UP TO 250°F)
- SO-SH, SO-PH HIGH TEMPERATURE STEAM OPTION (UP TO 300°F)
- 3-SS STAINLESS STEEL PUMP COVER



PHONE: (800) 246-9689 / (905) 761-1733 • FAX: (905) 738-6168
 WEBSITE: WWW.PSCCLEAN.COM • EMAIL: INFO@PSCCLEAN.COM

© 2002 PSC CLEANING SYSTEMS INC., ALL RIGHTS RESERVED